

COMBINED REBAR CUTTING AND BENDING MACHINES KOMBİNE İNŞAAT DEMİRİ KESME VE BÜKME MAKİNALARI

- Hidromekanik
- Max: 30 mm Kesim
- Max: 36 mm Büküm
- Düşük enerji tüketimi
- *Hydramechanical*
- *Max: 30 mm Cutting*
- *Max: 36 mm Bending*
- *Low energy consumption*



MAX 40



TECHNICAL SPECIFICATIONS

Model	En - Boy - Yük. (cm) W - L - H (cm)	Motor Gücü Motor Power (Kesme - Cutting) (kW)	Motor Gücü Motor Power (Bükme - Bending) (kW)	Motor Devri Rotation (rpm)	Mot. Frekansı Frequency (Hz)	Voltaj Voltage (V)	Ağırlık Weight (kg)	Hid. Yağ. Kaps. Hydraulic Oil Tank Capacity (lt)
MAX 40	110/98/110	2,2	3	1450	50	380	430	18

BENDING CAPACITIES

45 kg/mm ² Diameter (Ø) x Piece		65 kg/mm ² Diameter (Ø) x Piece		85 kg/mm ² Diameter (Ø) x Piece	
Ø 36 x 1	Ø 24 x 2	Ø 32 x 1	Ø 20 x 2	Ø 28 x 1	Ø 18 x 2

CUTTING CAPACITIES

45 kg/mm ² Diameter (Ø) x Piece	65 kg/mm ² Diameter (Ø) x Piece	85 kg/mm ² Diameter (Ø) x Piece
Ø 30 x 1	Ø 28 x 1	Ø 26 x 1